

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/036170 A1

(51) International Patent Classification⁷: **G01M 19/00**,
F28F 27/00

(DK). BENDTSEN, Christian [DK/DK]; Brogade 14, 1.,
DK-6400 Sønderborg (DK).

(21) International Application Number:
PCT/DK2003/000701

(74) Common Representative: **DANFOSS A/S**; Patent De-
partment, DK-6430 Nordborg (DK).

(22) International Filing Date: 14 October 2003 (14.10.2003)

(81) Designated States (*national*): AM, AT, AU, BA, BG, BR,
BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HR,
HU, IL, IN, IS, JP, KR, KZ, LT, LU, LV, MD, MK, MX,
NO, NZ, PL, PT, RO, RU, SE, SG, SK, TR, UA, US, UZ,
VN, YU, ZA.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 2002 01582 15 October 2002 (15.10.2002) DK

(84) Designated States (*regional*): Eurasian patent (AM, AZ,
BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,
IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(71) Applicant (*for all designated States except US*): **DAN-
FOSS A/S** [DK/DK]; DK-6430 Nordborg (DK).

Published:
— with international search report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **THYBO, Claus**
[DK/DK]; Helgolandsgade 33, DK-6400 Sønderborg

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: A METHOD AND A DEVICE FOR DETECTING AN ABNORMALITY OF A HEAT EXCHANGER, AND THE USE
OF SUCH A DEVICE

(57) Abstract: A method and a device for detecting an abnormality of a heat exchanger exchanging heat between a first fluid flow flowing in a conduit and a second fluid flow flowing along a flow path, said conduit and said flow path each having an inlet and an outlet, whereby the method comprises the steps of: establishing at least one parameter representative of the temperature conditions of the heat exchanger, establishing a second fluid inlet temperature, establishing a parameter indicative of expected heat exchange between the heat exchanger and the second fluid, processing the heat exchanger temperature, the second fluid temperature and the pa-
rameter indicative of expected heat exchange for establishing an estimated second fluid outlet temperature, employing the estimated second fluid outlet temperature for evaluating the heat exchange between the first and second fluids by comparing the estimated second fluid outlet temperature, or a parameter derived therefrom, with a reference value.

WO 2004/036170 A1